



INDUSTRIAL CYLINDER HEATED DRYING IRONERS

FCI800 | FCIR800 | FCIF800 | FCI800

FEATURES

- Large surface contact with linen
- Finger protection and emergency button for more safety
- Automatic cooldown
- Easy-to-operate microprocessor
- Overdimensioned fan for flexible installation
- Indication of ironing speed and temperature
- Reverse mode possible
- Frequency controlled motor
- Space saving installation against the wall is possible:
front return
- Electric, gas or steam heating
- Overheating check system



OPTIONS

- Stop pedal

OPTIONAL MODULES

- Model FCIR 800
Frontal and rear output
- Model FCIF 800
Module R with length folding
- Model FCIFF 800
Ironer with feeding and length folding
- Crossfolder and stacker



ROBUST
DESIGN



HIGH OUTPUT



MODULAR
SYSTEM

FCI 3186 / 800

ROLLER DIAMETER (MM)	807
USEFUL ROLLER LENGTH (MM)	3186
IRONING CAPACITY* (KG/H)	195
HEATING	
ELECTRICAL HEATING (KW)	75
GAS HEATING (KW)	110
STEAM HEATING (KG/H)	190
MOTOR	
ROLLER MOTOR (KW)	0,75
FAN MOTOR (KW)	2 x 0,55(50Hz) / 2 x 0,55 (60Hz)
FAN CAPACITY (M ³ /H)	2 x 1300
ROLLER SPEED (M/MIN)	3 - 15
ELECTRICAL CONNECTIONS	3AC / 380-415 +N / 50,60Hz 3AC / 380-415 -N / 50,60Hz 3AC / 440V / 60Hz 3AC / 208-240V / 50,60Hz
TRANSPORT DATA	
NET WEIGHT (KG)	2700 (E) / 3000 (S) / 2570 (G)
GROSS WEIGHT (KG)	2610 (E) / 2900 (S) / 2480 (G)
DIMENSIONS H X W X D (MM)	1985 x 4260 x 1915
PACKING DIMENSIONS H X W X D (MM)	2075 x 4330 x 1940

* Data from lab according to standard ISO9398-1. The actual capacity depends on laundry conditions and operators which could be 20% -40% lower.

