




ROLLER IRONER FOR ON-PREMISES LAUNDRY APPLICATIONS

I30-160

FEATURES

- Attractive design
- Standard finger guard protection
- When unattended, the device shuts off automatically
- Reduced number of mechanical and moving parts for a lower maintenance cost
- Homogeneous ironing pressure to ensure top ironing quality
- PID controlled temperature regulation offering better temperature distribution and reduced energy consumption
- Long-life heating elements
- Anodised extruded aluminium profile avoiding temperature drop and ensuring top ironing quality
- All vital components are easily accessible
- Standard NOMEX top cover sheet
- Backside of the basin is insulated with 25mm ceramic wool
 - no energy waste
 - quick temperature rise






OPTIONS

- Frequency inverter enabling variable ironing speed
- Fan exhaust

130-160

ROLLER DIAMETER (MM)	290
USEFUL ROLLER LENGTH (MM)	1600
IRONING CAPACITY (KG/H)	32-50 (rest humidity 20-25%)
SPEED (M/MIN)	3,9 (2-4 ^{**})
FUSES	
230/50/3	40 A
230/60/3	40 A
400/50/3	25 A
400/60/3	25 A
440/60/3	25 A
HEATING (KW)	13,2
TOTAL POWER (KW)	13,7 (13,9 ^{**})
EXHAUST FAN (M ³ /H)	200 (**)
TRANSPORT DATA	
NET WEIGHT (KG)	262
GROSS WEIGHT (KG)	300
DIMENSIONS H X W X D (MM)	1100 x 2200 x 500
VOLUME (M ³)	1,21
PACKING DIMENSIONS H X W X D (MM)	1260 x 2280 x 590
VOLUME (PACKED) (M ³)	1,69

(**) Option AV: variable ironing speed and exhaust



1. Control panel
2. Emergency stop button
3. Manual roller drive
4. Main switch and power supply