



# HIGH-SPIN HYGIENIC BARRIER WASHER-EXTRACTORS

IH180  
18KG

IH240  
24KG

IH280  
28KG

## FEATURES

- Freestanding, high spin
- Complete stainless steel cabinet
- Stainless steel drum and tub
- Aries Elite - Fully programmable
- Patented soap hopper
- Large drain valve (Ø 76 mm)
- Easy access to all important parts from all sides
- Large door opening for easy loading & unloading
- Automatic door positioning
- Liquid soap connection

## OPTIONS

- USB plug (on the side panel)
- Liquid soap pumps
- Water recovery option incl. second drain valve
- Steam heating version
- Water sample tap
- Aries Assist
- Second display
- Weighing system



HYGIENIC  
SOLUTION



LARGE DOOR  
OPENING



EASY  
OPERATION



LOW WATER  
CONSUMPTION



LOW ENERGY  
CONSUMPTION

	IH180	IH240	IH280
DRUM			
CAPACITY 10:1 (KG)	18	24	28
CAPACITY 9:1 (KG)	20	27	31
VOLUME (L)	180	240	280
DRUM DIAMETER (MM)	750	750	750
NUMBER OF DRUMS	1	1	1
NUMBER OF LOADING DOORS	1	1	1
NUMBER OF UNLOADING DOORS	1	1	1
DRUM SPEED			
WASH SPEED (RPM)	42	42	42
EXTRACTION SPEED (RPM)	939	939	914
G-FACTOR	370	370	350
PROGRAMMER			
ARIES ELITE	standard	standard	standard
CABINET			
STAINLESS STEEL	standard	standard	standard
HEATING			
ELECTRICAL (KW)	12 / 18	18	21,9
STEAM (BAR)	3-8	3-8	3-8
CONNECTIONS			
ELECTRICAL	STD: (C)380-415/50/60/3 OPT-NC: (Q)200-240/50/60/3 - (X)200-240/50/60/1 (only available for boiler fed and steam heating) - (P)380-415/50/60/3-(N)440-480/50/60/3		
WATER INLET (MM)	STD: 3 x 3/4" OPT-NC : 2 x 3/4"	STD: 3 x 3/4" OPT-NC : 2 x 3/4"	STD: 3 x 3/4" OPT-NC : 2 x 3/4"
STEAM INLET (MM)	13 (1/2")	13 (1/2")	13 (1/2")
TRANSPORT DATA			
GROSS WEIGHT (KG)	485	515	550
NET WEIGHT (KG)	430	460	490
DIMENSIONS H x W x D (MM)	1610 x 1010 x 1235	1610 x 1310 x 1235	1610 x 1240 x 1235

	A	B	C	D	E	F
IH180	900	1145	1455	655	1423	850
IH240	1020	1145	1455	675	1423	970
IH280	1130	1145	1455	670	1423	1080
	width	depth	height			

	Door dimensions	
IH180	325	376
IH240	325	496
IH280	325	496
	height	width

